

ICAR S.p.A.
Via Isonzo, 10
2090 Monza (MB) - Italia

Tel. +39 03983951
Fax. +39 039833227
www.icar.com
sales@icar.com



LNK-P2X-150-70



Model: LNK-P2X-150-70
Capacitance C (μ F): 150
Rated DC voltage (V): 700
Peak voltage (V): 1400
Max rms current (A): 85
Peak current (A): 5300
Self inductance (nH): 30
Series resistance (m Ω): 0,4
Thermal resistance with natural cooling ($^{\circ}$ C/W): 10
Full current not concentrated max working frequency (kHz): 10
Creepage between terminals (mm): 28
Clearance (mm): 28
Weight (kg): 0,45
Box qty (pcs): 16

Generalities

COMPACT DESIGN
LOW LOSSES
HIGH RIPPLE CURRENT
DRY TECHNOLOGY I.E. NO LEAKAGE PROBLEMS
SELF EXTINGUISHING RESINS AND PLASTICS ACCORDING TO UL94
On request, Requirement R22, Hazard Level HL2 according to EN 45545:2013 standard

Technical Info

The capacitor consists of metalized polypropylene windings filled with dry resin. This technology gives many advantages:

- high DC voltage load capability:
- high specific ratio capacitance to volume:
- high capability to withstand surge currents:
- very good self healing characteristics.

Capacitance tolerance: $\pm 10\%$, $\pm 5\%$ on request
Useful life: 100.000 hrs at 70° C hot-spot and U_n
Failure rate: 100FIT
Operating Temperature -40° C / $+70^{\circ}$ C .
Maximum hot spot 85° C
UL file: E191589

ICAR S.p.A.
Via Isonzo, 10
2090 Monza (MB) - Italia

Tel. +39 03983951
Fax. +39 039833227
www.icar.com
sales@icar.com



LNK-P2X-150-70

Image not found or type unknown

