

## **Sending card**

### **TS902**

V1.1

Jan 2019

TS902 is a sending card with four network ports, and supports single, double and full color LED screen. It also supports 4K video source input and its maximum capability is 2.6 million pixels.

#### **1. Features:**

- 1) One Audio signal input;
- 2) One PCI-E 1X interface;
- 3) One DVI video signal input;
- 4) One HDMI video signal input;
- 5) Supports 4K video source input;
- 6) Supports RCG file read-back function;
- 7) Supports RCG file broadcasting function;
- 8) Supports CON file broadcasting function;
- 9) Supports 12bit/10bit/8bit video input;
- 10) Supports 16bit grey scale;

Official website: [www.linsn.com](http://www.linsn.com)

Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd,  
Nanshan District, Shenzhen

Tel: +86-0755-86183590/ 4008836968

- 11) With four network output ports, supports common video source, like 2560x1024, 1920x1200, 2048x1152, etc;
- 12) Supported video format: RGB, YCrCb4:2:2, YCrCb4:4:4.

## 2. Appearance



Official website: [www.linsn.com](http://www.linsn.com)

Add: Floor 15&16, Jiajiahao Business Building, No. 10168, Shennan Blvd,  
Nanshan District, Shenzhen

Tel: +86-0755-86183590/ 4008836968



### 3. Working conditions

Rated voltage (V)	5	maximum	5.5	minimum	4.5
Rated current (A)	0.50	maximum	0.57	minimum	0.46
Rated power consumption(W)	2.5	maximum	3.1	minimum	2.1
Working temperature (°C)	-20°C ~ 70°C				
Working humidity (%)	0% ~ 95%				

**END**