

PAINEL DE LED P4.8

OUTDOOR BRIWAX

ESPECIFICAÇÃO

P4.81 outdoor Led Display		
Pixel Pitch: 4.81 (mm)	Module size: 250X250 (mm)	Cabinet size: 500x500 (mm) etc
Pixel Density: 43264/m ²	Color Configuration: 1R1G1B	Module Resolution 52*52=2704(DOTS)
Module Weight: 0.5 kg	Led Lamp: Hongsheng, Nationstar etc	Driving IC: ICN2153/SM16380 etc
Cabinet Resolution: 104*104 etc	Cabinet area: 0.25m ² etc	IP Level: IP65
Main specification		
Best View distance: $\geq 4.81m$	Horizontal $\geq 160^\circ$	Vertical: $\geq 140^\circ$
Average power consumption $\leq 250W/m^2$	Max power consumption $\leq 600w/m^2$	Module Max consumption $\leq 25W$
Certificate: ISO9001, CE, RoHS, CCC etc	Driver Mode 1/13s	
Refresh $\geq 1920Hz$	Brightness $\geq 3500cd/m^2$	Frame frequency $\geq 60Hz$
Module IC Qty: 48Pcs	IC: SM16380/ICN2153 etc	16 levels adjustable
Software Brightness adjustment: 255 Degree adjustable		
Control System		
Synchronous/Asynchronous control		
Trouble Free Time $\geq 5000H$	Life span 75000~100000H	Pixel runaway rate $< 0.0002PCS$
PH4.81-13S	SMD 3 IN 1	LED encapsulation: SMD1921