



K2.5 indoor fixo-Specifications

	Parameter	Parameter
Physical Parameter	LED Type	SMD 2020
	Pixel Pitch (mm)	2.5mm
	Panel Dimensions (WxHxD)/(mm)	640*480*60
	Pixel Per Panel	256*192
	Resolution per gabinete	49152
	Panel Weight (kg/gabinete)	7
	Panel Material	AL Die-casting
	Module Dimensions (WxH)/(mm)	320*160
Optoelectronic Parameter	Brightness (nit)	600-800
	Refresh Rate (Hz)	3840-7680
	Gray scale (bit)	14-16
	Contrast Ratio	5000:1
	Viewing Angle (H/V) (°)	160/140
	Driving Type	1/32
	AC Operating Voltage (V)	200-240V
	Power Consumption (Avg/Max.)(W/m ²)	150/450 W/m ²
Application Parameter	Operating Temperature (°C)	- 20~ + 40
	Operating Humidity (RH)	10 % ~80 %
	IP Rating (Front/Rear)	IP21
	LED Lifetime (H)	100000
	Module Maintenance	Front
	PSU & Others Maintenance	Front
	Panel Installation Type	Stacking/Wall-mounting

Remark :Power consumption tolerance: $\pm 15\%$, according to the actual situation.