





PAINEL DE LED VAZADO

OUTDOOR ONE**LIGHT**

Model		JL3-7	JL5-10	JL10	JL15.6
Module	Module image				
	Pixel Pitch(mm)	W:3.9 H:7.8	W:5.2 H:10.4	W:10.4 H:10.4	W:15.6 H:15.6
	Transparency	55%	65%	65%	80%
	Pixel (dot/m ²)	32768	18432	9216	4096
	Driver chip	ICN2153PWM	MY9866	MY9866	ICN2038S
	Scanning method	1/8	1/4	1/2	Static
	Refresh rate(hz)	5120	3840	3840	30000
	Brightness(cd/m ²)	≥4500	≥4500	≥4500	≥4500
	LED specification	SMD1921	SMD1921	SMD2727	SMD2727
	Best viewing distance/m	4	6	10	15
	Maximum viewing angle	140°			
	LED lamp life	≥100,000 hours			
	LED pixel composition	RGB 3 in 1			
Cabinet	Cabinet connection	Fast lock			
	Cabinet material	Die cast aluminum			
	Maintenance	Front / Rear			
	Protection grade	IP65			
	Cabinet size(mm)	1000*500*80			
	Cabinet weight	15kg/m ²			
	Grayscale level	14bit			
Screen	Color temperature	3000k/12000k Adjustable			
	MTBF	≥ 6500 hours			
	Working temperature	-20~60°C / 20%~90%			
	Storage temperature	-15~55°C / 10%~90%			
	Shadow removal	System standard			
	LED control system	Nova			
	Data connection	WiFi / DVI / HDMI / DP / USB/RJ45network remote control			
	Input voltage	AC100~240V 50/60Hz			
	Maximum Power(W/m ²)	800			
	Average Power(W/m ²)	240			
	Installation method	Hanging (10 cabinets vertically) /base installation/fixed installation			
	Packing	Wooden box or flightcase			