

# HCH-3033-CHG

## Charger Specifications:

### Temperature Limits:

Operating Range: 0°C to 40°C  
 32°F to 104°F  
 Storage Range: -10°C to 50°C  
 14°F to 122°F

### Dimensions:

Length: 420 mm  
 Width: 160 mm  
 Height: 108 mm  
 Weight: 1150 g

### Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 24 months from date of shipment under normal use.



## Compatible Batteries

HMC3X00-Li(S) GTS Battery  
 HMC3000-LAS-Li GTS Battery

- Highest quality cells used
- Longer cycle life
- Extremely rugged
- Rigorous testing



Trademarks are the sole property of their respective owners.

14.05.16

## 3 Bay Cradle & 3 Bay Battery Charger

**Dual-chemistry charger**  
 Supports Li-Ion and Li-Polymer chemistries.


Includes power supplies and cable.

**More efficiency in less space**  
 Charges three spare batteries plus the batteries in three devices simultaneously and fast

Made of highly rugged aerospace grade aluminum housing.



**Tri-color charging indications**  
 A charging LED indicates charging status.



**Hassle-free mounting**  
 Utilizes same mounting bracket as Symbol® chargers for easy wall mounting.

Can easily be customized to meet your customer needs.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.  
 550 Cochituate Road Framingham, MA 01701  
 US: 1.800.267.2711 ■ EU: 00800.5390.5390  
[www.GTSpower.com](http://www.GTSpower.com) @GTSpower1

