

HMC9500-Li Battery

Features:

- Intelligent battery with onboard fuel gauge and state of health indicator.
- Contains the highest quality battery cells.
- Provides excellent discharge characteristics.
- Rigorous testing including temperature, vibration, shock, drop, short circuit and overcharge.

Cell Specifications

Chemistry:	Li lon
Voltage:	3.7 volts
Capacity:	4800 mAh

Environmental Data

Charging Temp.:	0° - 40°C (32°F to 104°F)
Discharging Temp.:	0° - 40°C (32°F to 104°F)

Rechargeable battery for Motorola MC9500/MC9590 devices.

Replaces OEM BTRY-MC95IABA0 batteries.



Battery Dimensions

Length:	23.0 mm	
Width:	48.0 mm	
Height:	115.0 mm	



Each battery is guaranteed to be free from defects in materials and workmanship and can maintain a minimum of 80% of its rated capacity for 12 months from date of shipment under normal use.

About Us

Global Technology Systems, Inc. ("GTS") is the trusted expert in mobile power technology. GTS designs and manufactures high-performance batteries, chargers, and power management technologies for essential mobile devices. Millions of public safety, government, military, and business professionals rely on GTS to power mission critical communications and mobile computing applications. Founded in 2000, GTS is headquartered in Framingham, Massachusetts.



www.GTSpower.com @GTSpower1