

SWT-P-162-480B

16 Port PoE+ Switch



Key Features

- Conforms to IEEE802.3, IEEE802.3u, IEEE802.3af, IEEE802.3at
- Provides (16) 10/100/1000M Base-TX ports and (2) 1000M Combo RJ45/SFP Base-TX Uplink Ports
- High back-plane bandwidth 36Gbps
- IEEE802.3x Flow control
- Plug and play operation
- Surge protection for power port and data ports
- EMI standards complies with FCC, CE class B
- 2 Year Warranty

SWT-P-162-480B

Fixed Port	16 10/100/1000M Base-TX ports 2 Combo RJ45/SFP ports
LED Indicators	PWR, PoE, Link/Act VLAN LED
Thermal Methods	Built-in Noiseless Fan
Switching Capacity	36G.
MAC Address Table	8K
Traffic Control	IEEE 802.3x full-duplex ow control
Included Accessories	Rack ears
PoE	
PoE Port	(16) 10/100/1000M Base-TX ports
PoE Standard	IEEE802.3af, IEEE802.3at, per port 30W (16) ports
ENVIRONMENTAL	
Operating Temperature	0°C to 40°C (32°F to 113°F)
Storage Temperature	-40°C to 70°C (40°F to 158°F)
Operating Humidity	10% ~ 85% (non-condensing)
ELECTRICAL	
Power	100V~240V AC, 50/60 Hz
Power Consumption	500W
MECHANICAL	
Dimension (WxHxD)	13.5" x 1.65" x 7.2"
Weight	7.4 lbs

* Design and specifications are subject to change without notice.