

Mastertac Technical Information

03-04-2020 EN SI

Face	PE LASER M HS
Sales Code	AXV
Product	White matt high pigmented computer imprintable polyethylene film.
Use	Information labelling where overprinting is made by laser, digital offset, dot-matrix or thermal transfer. Recommended for drum and logistics labelling. Specially developed for medium and high volume laser printers.

Typical technical values

Substance	115	g/m ²	DIN 53352
Caliper	178	µm	DIN 53370
Elongation MD	430.0	%	DIN 53455
Elongation CD	470.0	%	DIN 53455
Opacity	92	%	DIN 53146/1

Printability Due to the surface properties, the film is pre-printable by screen, offset, flexography, letterpress, elctrophotography, electrography, digital offset and dotmatrix. Thermal transfer with selected ribbons. Inks for filmic substrates are recommended. Laser and copier printable: specially developed for medium and high volumes.

Disclaimer The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.