

Premier Proximity Cards

CREATE CUSTOM, PRE-PRINTED AND PROGRAMMED CARDS

Zebra Premier Proximity Cards enable customers to create custom, pre-printed and programmed cards with any Zebra card printer*. The cards have a read range of up to 5 inches so users can scan their cards without removing them from badge holders, wallets and purses. The cards offer universal compatibility with proximity card readers.



125 KHz Contactless Low-frequency Technology 26 Bit – 37 Bit Programmable When used in an access control application, Zebra Premier Proximity Cards are an effective way to protect company personnel and assets by restricting access to buildings, rooms or other secure locations.

Meeting ISO standards for thickness, these durable cards are made of high-quality PVC to be strong, yet flexible, and resistant to cracking and breaking. Additionally, they feature a printable PVC surface with a glossy finish. Zebra Premier Proximity Cards provide consistent high-quality printed cards every time.

Sold in boxes of 500, the cards can be formatted and pre-programmed with an external number for easy identification and control. And, the cards support 26-37 bit encoding and accept either a horizontal or vertical slot punch for integration into customers' current access control systems.

Premier Proximity Cards Specifications

GENERAL SPECIFICATIONS

- Size: CR80 (3.375" x 2.125")
- Thickness: 30mil +/- 10%
- Construction: High-quality PVC, Graphics Quality
- Color: White aGloss
- Packaging: 500 Cards/Sleeve
- Technology: Contactless LF (Low Frequency) Proximity Card
- Frequency: 125 KHz
- Read Range: 2" 5"
- Compliance: ISO/IEC 7810, ISO/IEC 14443

FORMATS

26-Bit Standard 34-Bit 35-Bit Corporate 1000 36-Bit 37-Bit

OPTIONS

Custom Pre-printing Security Features Magnetic Stripe Slot Punching Pre-programming **FEATURES** Offers universal compatibility with proximity card readers. Can be formatted and programmed with an external number for easy identification and control. Custom pre-printing and programming available.

Meets ISO standards for thickness.

Qualified for use with all Zebra Card printers.

Accepts either a horizontal or vertical slot punch.

Strong, flexible and resistant to cracking and breaking.

Specifications subject to change without notice.

* Zebra printers do not encode proximity cards. Cards must be pre-encoded or encoded using a third-party external encoder.

For more information about the Premier Proximity Cards, visit www.zebra.com or access our global contact directory at www.zebra.com/contact

NA and Corporate Headquarters +1 800 423 0442 inquiry4@zebra.com Asia-Pacific Headquarters +65 6858 0722 contact.apac@zebra.com EMEA Headquarters zebra.com/locations mseurope@zebra.com Latin America Headquarters +1 847 955 2283 la.contactme@zebra.com

©2016 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. 04/2016

Ideal for These Applications

- Access control
- Identity management
- Asset
 management