

# Tech Specs

UniFi UIISP Branding

UniFi Cloud Gateways WiFi Switching Cloud Keys & Gateways Camera Security Door Access Phone System New Integrations Accessories

## Camera Security / AI Professional

Datasheet

Installation Guide

Marketing Images



### Mechanical

<b>Dimensions</b>	Without mount: Ø86 x 112.6 mm (Ø3.4 x 4.4") With mount: Ø86 x 175.3 mm (Ø3.4 x 6.9")
<b>Weight</b>	Without mount: 675 g (1.5 lb) With mount: With mount: 820 g (1.8 lb)
<b>Enclosure materials</b>	Aluminum alloy, polycarbonate
<b>Mounting material</b>	Aluminum alloy
<b>Weatherproofing</b>	IP65
<b>Resistance</b>	IK04

### Optics

<b>Sensor</b>	1/1.8" 8MP sensor
<b>Lens</b>	F 4.1—12.3 mm; f/1.53 -f/3.3
<b>View angle</b>	Wide: 109.9° (H), 59.9° (V), 127.7° (D) Zoom: 34.9° (H), 19.7° (V), 40° (D)
<b>Night mode</b>	Built-in IR LED illumination and an IR cut filter

---

## Video

Video compression	H.264
Resolution	8MP 3840 x 2160 (16:9)
Max. frame rate	30 FPS
Image settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay, HDR

---

## System

Processor	Quad-core Arm® Cortex®-A53 based chip
Networking interface	GbE RJ45 port
Max. power consumption	11W
Power method	PoE
Supported voltage range	37—57V DC
LED	R/G/B/W ring
Button	Factory reset
Mounting	Wall, ceiling, pole mount
Operating temperature	-20 to 50° C (-4 to 122° F)
Operating humidity	0 to 90% noncondensing
Certifications	FCC, IC, CE

---

## Audio

Microphone	Yes (Can be disabled)
Speaker	Yes

---

## Software

Web application	UniFi Protect
Mobile app	UniFi Protect iOS™ and Android™

### Stay in Touch

<input type="text" value="Email"/>	<input type="button" value="Subscribe"/>
------------------------------------	--

