

[Get a Quote](#)

Overview

The Switch 8 PoE 150W (US 8 PoE 150W), a fully managed switch with (8) GbE RJ45 ports and (2) 1G SFP port. Each of the switch's ports can provide either 802.3at PoE+ or configurable, 24V passive PoE to UniFi access points or other PoE devices.

Quick Specs

Figure 1 shows the appearance of US-8-150W.



Table 1 shows the Quick Specs.

Product Code	US-8-150W
Power Supply	AC/DC, Internal, 150W DC
Networking Interfaces	(8) 10/100/1000 Mbps RJ45 Ports (2) 1 Gbps SFP Ports
Management Interfaces	Ethernet In-Band
Dimensions	204 x 43 x 235 mm (8.03 x 1.69 x 9.25")

Product Details

Figure 2 shows the front panel of US-8-150W.



Figure 3 shows the back panel of US-8-150W.



US-8-150W provides these features:

- (8) GbE, 802.3at PoE+ and 24V passive PoE RJ45 ports
- (2) 1G SFP ports
- 130W total PoE supply

Compare to Similar Items

Table 2 shows the comparison of US-8-150W.

Module	US-8-150W	US-16-150W
Networking Interfaces	(8) 10/100/1000 Mbps RJ45 Ports (2) 1 Gbps SFP Ports	(16) 10/100/1000 Mbps RJ45 Ethernet Ports (2) 1 Gbps SFP Ethernet Ports
Management Interfaces	Ethernet In-Band	Ethernet In-Band
Operating Temperature	-5 to 45° C (23 to 113° F)	-5 to 40° C (23 to 104° F)
Operating Humidity	5 to 95% Noncondensing	5 to 95% Noncondensing
Dimensions	204 x 43 x 235 mm (8.03 x 1.69 x 9.25")	443 x 43 x 221 mm (17.44 x 1.69 x 8.70")

Get More Information

Do you have any question about the **US-8-150W**?

Contact us now via [Live Chat](#) or sales@router-switch.com.

Specification

US-8-150W Specification	
Dimensions	204 x 43 x 235 mm (8.03 x 1.69 x 9.25")
Networking Interfaces	(8) 10/100/1000 Mbps RJ45 Ports (2) 1 Gbps SFP Ports
Management Interfaces	Ethernet In-Band
Power Method	100-240VAC/50-60 Hz, Universal Input
Power Supply	AC/DC, Internal, 150W DC
Max. Power Consumption	
Including PoE Output	150W

Excluding PoE Output	20W
Processor Specs	ARM Cortex-A9 400 MHz
Memory Information	256MB DDR3
Code Storage	32 MB NOR Flash
Line Rate	10 Gbps, Non-Blocking
LEDs	
System	Status
RJ45 Data Ports	PoE; Link/Speed/Activity
SFP Data Ports	Link/Speed/Activity
PoE Output (RJ45 Ports)	IEEE 802.3at/af 2-Pair (+1, 2; -3, 6); Passive 24V/0.7A 2-Pair (+4, 5; -7, 8)
ESD/EMP Protection	± 24kV Air, ± 24kV Contact
Shock and Vibration	ETSI300-019-1.4 Standard
Operating Temperature	-5 to 45° C (23 to 113° F)
Operating Humidity	5 to 95% Noncondensing

Want to Buy

Order Now

Get a Quote

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com