

TEMPINSPECT USB MULTI-USE DATA LOGGER

Data logger type	Multi-Use data logger
Temperature range minimum to maximum	-30°C to +70°C (-22°F to 158°F)
Accuracy	±0.10°C (+35.8 °C to +41 °C) ±0.13°C (+20.0 °C to +70.0 °C) ±0.25 °C (-40 °C to +125 °C)
Storage capacity	30,000 measurements
Battery life	Minimum 2 year
	1 minute, 5 minutes, 10 minutes
Standard	15 minutes, 30 minutes, 1 hour
measurement interval (configurable)	2 hours, 3 hours, 4 hours
	User may also customize as per needs
Temperature ranges	User can customize range
Delay	User can customize start delay
Recording time	Up to 2 years
Startup method	Manual start, or customizable via software
Stop method	Manual stop or automatically when full
Protection class	IP 65 (splash-proof)
Dimensions	65mm x 38mm x 16mm [L x W x H]
Weight	approx. 20g
Automatic report	PDF (chart + raw data) and CSV
Certifications	CE, ROHS, Reach

VIA DUFOUR 4, 6900 LUGANO SWITZERLAND,

INFO@COLDCHAINVISON.COM, WWW.COLDCHAINVISION.COM



Manual programming	Option to pre-program logger via software and then block manual programming with custom settings
PC connection	USB 2.0, Type A
REUSABLE	yes
Exception alarm	Yes