

LA·CO®

LEAK-TITE BLUE

Economical thread sealant with PTFE

This blue sealant is excellent for sealing water, air, steam, natural gas, refrigerants, gasoline, and ammonia.




FEATURES

- Pressures: 1,500 PSI (102 BAR) for gas; 5,000 PSI (340 BAR) for liquid
- Sealing temperature: -50°F to 500°F (-46°C to 260°C)
- Contains PTFE particles for greater sealing power
- Will not harden or dry out over time, remaining flexible for easy disassembly
- Safe, non-toxic, contains no solvents
- Washes off hands and clothes easily; quick and easy cleanup



Certified to NSF/ANSI 61-G



- Metal
- PVC



- Production Lines
- Fabrication Shops



Part No.	Size
046009	4 oz. Brush-in-cap
046029	16 oz. Brush-in-cap



DO NOT USE ON OXYGEN SERVICE; USE OXYTITE PASTE OR SLIC-TITE PTFE TAPE

FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® piping systems and products made with TempRite® Technology.™ "The FBC System Compatible Logo, FBC™, FlowGuard Gold®, BlazeMaster®, Corzan®, and TempRite® are trademarks of Lubrizol Advanced Materials, Inc. or its affiliates.

v1.23

MADE IN USA ★



JOACEL
COMÉRCIO & REPRESENTAÇÃO

